

WATER METERS EQUIPPED WITH AN IMPULSE-EMITTING DEVICE

All models can also be supplied just with pre-arrangement for impulse-emitting device

- ❑ Accuracy class: 2
- ❑ **BFUL model** from DN. 15 to DN. 40
single jet – wet dial – temp. classes T30 e T50
- ❑ **PFUL model** from DN. 15 to DN. 40
single jet – liquid-filled sealed counter – temp. classes T30 e T50
- ❑ **SFUL and AFUL models** from DN. 15 to DN. 40
single jet – dry dial – temp. classes T30 e T50
- ❑ **SCUL and ACUL models** from DN. 15 to DN. 40
single jet – dry dial – temp. classes T70 e T90
- ❑ **BFML model** from DN. 15 to DN. 50
multi jet – wet dial – temp. classes T30 e T50
- ❑ **PFML model** from DN. 15 to DN. 50
multi jet – liquid-filled sealed counter – temp. classes T30 e T50
- ❑ **AFML model** from DN. 15 to DN. 50
multi jet – dry dial – temp. classes T30 e T50
- ❑ **ACML model** from DN. 15 to DN. 50
multi jet – dry dial – temp. classes T70 e T90
- ❑ **WELF model** from DN. 50 to DN. 300
helical vane (Woltmann) – dry dial – cold water up to 50°C
- ❑ **WELC model** from DN. 50 to DN. 300
helical vane (Woltmann) – dry dial – hot water up to 130°C



For hydraulic performances and tecnica data please refer to the concerned water meter sheet (ex. For SCUL see SCU sheet).

multi jet and single jet pulse rates (pulse value must be stated when ordering):

0,25	0,5	1	2,5	5	10	25	50	100	250	500	1000
------	-----	---	-----	---	----	----	----	-----	-----	-----	------

helical vane (Woltmann) pulse rates (pulse value must be stated when ordering):

WELF model from DN. 50 to DN. 125 – cold water	WELF model from DN. 150 to DN. 300 – cold water
Reed switch sensor: K10 – K100 – K1000	Reed switch sensor: K100 – K1000 – K10000
Opto sensor + converter: analog power supply output 4/20 mA – 0/20 mA – 0/10 V	Opto sensor + converter: analog power supply output 4/20 mA – 0/20 mA – 0/10 V
Opto sensor + divider: from K100 to K1000	Opto sensor + divider: from K1000 to K10000
Opto sensor + converter with display: instant flow rate reading	Opto sensor + converter with display: instant flow rate reading
WELC model from DN. 50 to DN. 125 – hot water	WELC model from DN. 150 to DN. 300 – hot water
Reed switch sensor: K100 – K250	Reed switch sensor: K1000 – K2500
Opto sensor + converter: analog power supply output 4/20 mA – 0/20 mA – 0/10 V	Opto sensor + converter: analog power supply output 4/20 mA – 0/20 mA – 0/10 V
Opto sensor + divider: from K100 to K1000	Opto sensor + divider: from K1000 to K10000
Opto sensor + converter with display: instant flow rate reading	Opto sensor + converter with display: instant flow rate reading

Continuous development of our products may necessitate changes in details without prior notice – 05/16



G2 misuratori S.r.l. -
Via San Martino, 38 – 14100 ASTI (AT) – ITALY
Tel. +39.0141.721787 – Fax +39.0141.702280
E-mail: info@g2misuratori.it
[Http://www.g2misuratori.it](http://www.g2misuratori.it)



Branch office for Italy Centre Sud Area
Via Fontanelle, 3 – 00020 RIOFREDDO (RM) – ITALY
Tel. e Fax +39.0774.920216
E-mail: centrosud@g2misuratori.it

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV GL
= ISO 14001 =